

FLEX		Specification Sheet					Editor		
		Item No.: FLEX					Features		
		13 gauge red polyester shell, with black wrinkle latex coated on palm					High grip level, light shell, suitable for gardening, handling, construction etc. latex is very soft when grabbing, bending fingers.		
Product information							Picture		
Material/ Color/ Component ratio	Coating Composition and color	Latex							
	Liner Composition and Color	polyester							
	Overlock Composition and Color	Polyester According to customer's request							
	component ratio of shell	100% polyester							
Dimensional Parameters	Size	Total Length (mm)	Palm Width (mm)	Middle Finger Length (mm)	Glove Weight (g/pair)	Hem Color			
	6/XS	—	—	—	—				
	7/S	—	—	—	—				
	8/M	240	90		48	Green			
	9/L	250	98		56	Grey			
	10/XL	260	101		60	Yellow			
	11/XXL	270	105		64	Brown			
	tolerance	±8	±5	±3	±3				
EN388 2016	Abrasion(Circle)	2	EN407	Burning behavior level	—	EN511 2006	Convective cold		—
	Blade Cut(Coup test)	1		Contact heat level	—		Contact cold		—
	Tear(N)	2		Convection heat level	—		Water permeability in less than 30 minutes	—	
	Puncture(N)	1		Radiant heat level	—				
	ISO13997	X		Small splash molten metal	—				
	—	—		Large quantity molten metal	—				