

<b>XTREME CUT F</b>	<b>Specification Sheet</b>				Editor	
	Item No.: XTREME CUT F				Features	
	13 gauge cut resistant level-F shell, with black foam nitrile coating on palm				Cut level F provide top-level protection with enhanced comfort on hands oil proof, high abrasion, breathable	

Product information	Picture
---------------------	---------

Material/ Color/ Component ratio	Coating Composition and color	Water-based PU						
	Liner Composition and Color	HPPE, steel fiber						
	Overlock Composition and Color	Polyester According to customer's request						
	component ratio of shell							
Dimensional Parameters	Size	Total Length (mm)	Palm Width (mm)	Middle Finger Length (mm)	Glove Weight (g/pair)	Hem Color		
	6/XS	—	—	—	—			
	7/S	—	—	—	—			
	8/M	240	98		73	Green		
	9/L	250	102		82	Grey		
	10/XL	260	104		90	Yellow		
	11/XXL	270	108		93	Brown		
	tolerance	±8	±5	±3	±3			
EN388 2016	Abrasion(Circle)	4	EN407	Burning behavior level	—	EN511 2006	Convective cold	—
	Blade Cut(Coup test)	X		Contact heat level	—		Contact cold	—
	Tear(N)	4		Convection heat level	—		Water permeability in less than 30 minutes	
	Puncture(N)	4		Radiant heat level	—			
	ISO13997	F		Small splash molten metal	—			
	—	—		Large quantity molten metal	—			